

# Parkland Racing Association Inc.

P.O. Box 902  
Yorkton, SK  
S3N 2X1

## **Demo Derby Rules:**

### Vehicle Preparation:

#### **Items that MUST be removed:**

- all glass
- lights
- trims
- grill
- upholstery
- trailer hitches
- fuel tanks
- air conditioner must be discharged

#### **Required Modifications:**

1. Fuel tank must be removed, and a fuel cell must be securely fastened in the rear seat area of the car. This tank must be made of steel and mounted with metal straps. Metal boat tanks are suitable.
2. Battery must be removed from stock location and relocated on the passenger side floor of the car. The battery must be enclosed in a box, and bolted to the floor of the car with bolts and washers. Marine box is suitable retained with steel straps.
3. Hoods and trunks must be bolted, chained, or bolted with ready rod. The hood and trunk may have up to 4 ready rods each, 2 through the frame, and 2 through the body using large washer plates that do not exceed 6" in diameter. Welding of the trunk is permitted.
4. Fire access holes must be cut into the hood on either side of the carb, minimum 8" maximum 10" holes.
5. Doors may be chained or bolted shut. Welding of the doors is permitted.
6. Engine must remain stock, motor mounts may be strengthened. Exhaust must be vented free from the engine compartment. Flame arresters must cover the carb intake.
7. Radiator must be in stock location. Fan may be removed.
8. Transmission lines must be connected together if rad is removed. Dipstick must be removed, and a piece of hose connected and ran to the ground to prevent fires.

9. Tranny coolers are permitted. Must have all hose connectors covered and secure. Any lines running through the car must be covered with garden hose or another kind of hose.
10. Bumpers must be original equipment. No inverted bumpers, bumpers may be chained up and corners trimmed.
11. Seat belts must be a minimum 3 point, and in good shape.
12. Tires maximum 8 ply, steel rims and maximum one tube per tire. No studded tires.
13. All drivers must wear a DOT approved helmet at all times while in the vehicle. Eye protection is recommended.

### **Optional Modifications:**

1. Driver's Door must have a door bar bolted at medium height with minimum three  $\frac{3}{4}$ " bolts. This door bar must be a minimum 6" C-channel. Maximum length of bar, 6'6".
2. Passenger's Door may also be fitted with a door bar.
3. Dash bar extending door to door above steering column. Must be bolted with  $\frac{3}{4}$ " bolts or larger with steel plates on outside of the door.
4. 2- 12volt batteries allowed.
5. Electric fuel pumps permitted. Must be on it's own clearly marked power switch in reach of driver.
6. Floor shifters may be cut through the floor, with a minimum size hole.
7. Head post from the floor to the top of the roof supporting the driver's seat must be bolted with a minimum of 3 bolts top and bottom.
8. Rear support bar, from door bar to door bar behind front seat must be bolted with  $\frac{7}{8}$ " bolt or larger. This bar may also be attached to the head post.

### **ABSOLUTELY NO:**

1. Imperials, hearses, ambulances, convertibles, or T-tops.
2. Altering of suspension
3. Holes larger than 3" through fire wall
4. Foul language on car.

